



CINAJUS Pty Ltd

ABN 86 089 623 487

StoneFloors & StoneWalls

32 Bryant Street, Padstow NSW 2211
Tel: (02) 9773 5677 Fax: (02) 9773 5644

Email: info@cinajus.com

Online catalogue: www.cinajus.com

CINAJUS NATURAL STONE

Product disclosure statement

At Cinajus we stock over 5000 square meters of 100% Natural Stone as tiles, pavers and wall cladding on an everyday basis for immediate delivery.

Granite Bluestone Basalt Limestone Sandstone Travertine

Points to consider when buying natural stone.

Buyers should be aware that natural stones are a product of nature and therefore variation in thickness, dimension sizes, tones and colour is inherent over and above the specifications and samples.

We have a rigorous quality control system and we take great care in checking the material prior to dispatch from the quarries, however being a natural product there could be minor variations in dimensions and thickness.

Buyers should be aware that there could be some material with minor chips due to the weight of the stone and the distance of transportation. These chipped pieces are generally used for cutting. We suggest that you order the industry standard of 10% extra to allow for wastage and cutting on site and spares.

This is true all for all natural stone tiles, pavers and cladding regardless of its origin and is no different to ceramic, porcelain or vitrified tiles or brick or concrete pavers.

- Samples only represent the general characteristics of the stone.
- We recommend you test the material for suitability of application.
- Sealing is recommended for all natural stone products.
- Pre-sealing of sandstone and limestone is recommended prior to installation around a salt water pool.
- Do not use any acid wash to clean any natural stone.
- A pH neutral cleaner is recommended.

Applications

Driveways – Granite, Balmoral Basalt or Bluestone either in a cobblestone or a paver minimum 30mm thick to be laid on a concrete slab.

Internal Tiles – 15mm or 20mm thick stone.

Pool coping – 30 or 40mm thick stone Bullnozed or beveled edge.

Paving – Pool surrounds, patios, balconies or anywhere else except vehicular trafficable areas – 20mm thick stone.

Walling internal or external - 10mm and upwards thick stone.

We recommend our stone pavers be laid on a concrete slab with a sand cement moist mortar or suitable glue which will allow for minor variations in the dimensions and thickness of the stone.

Before undertaking any flooring or walling project please consult a licensed tradesperson or contact us and we will assist you with the selection of the most appropriate product for your application.